

L801 Specifications

Printer:

Print method:	Memjet Waterfall Printhead Technology® 11 Integrated Circuit (IC) Chips – 70,400 nozzles
Inks:	Dye-based, 250 mL CMYKK (1.25 L total) — Watershield water-resistant formula available
Print resolution:	1600x1600 dpi or 1600x800 dpi
Print speed:	6"–12" per second (152 mm–305 mm)
Print width:	8.5" (216 mm)
Cutter/sheeter:	Powered

Media:

Media/Label Size:	Width: 2"–8.5" (50.8 mm–216 mm) Length: 2"–48" (50.8 mm–1220 mm)	Media sensors:	Gap, continuous, black mark
Media Thickness:	Minimum 0.005" (0.13 mm) Maximum 0.01" (0.3 mm, including liner)	Die-cut gap:	Minimum 0.125" (3.0 mm) Maximum 0.3" (8.0 mm)
Core diameter:	Requires 3" (76.2 mm) cardboard core	Black mark:	(3 mm wide, 25.4 mm long on left)
Outside diameter:	Maximum 8" (203 mm)	Substrates:	Compatible with a wide range of paper, polyester, polypropylene, and vinyl label stocks

General:

Interfaces:	USB 2.0, TCP/IP (Manual IP configuration or DHCP), GPIO available for external device control
Operating system:	Windows 7+ (32 and 64 bit)
Barcode font:	1D Barcode at least Grade B (Code39) with 10mils bar width
2D code printing:	2D Barcode at least Grade B (PDF417) with 10mils cell size
Operating temperature:	15°–35° C (59°–95°F) at RH 20–80%
Overall dimensions:	18.9" (480 mm) W, 19" (485 mm) D, 21.1" (535 mm) H
Weight:	83 lb (37.6 kg)
Rated voltage:	AC 110V – 220V, auto-sensing
Warranty:	One year



Available with
roll-to-roll
rewind unit



In-House Label Solutions for Every Level of Production


afinialabel.com

Your Local Dealer:

US Office
sales@afinialabel.com
+1 888.215.3966



UK Office
sales@afinia.co.uk
+44 (0) 845.250.7949



WALZ
Label & Mailing Systems
624 High Point Ln, East Peoria, IL 61611-9329
(309) 698-1500 T/F (877) 971-1500
www.walzeq.com